



2. remove weather striping, but stop pulling it off at around 60% of the way to the other side. you may have to remove a strip of black foam from the left side area, no big deal.

3. use a light to keep that cowl up! it's a no brainer, you need light in there, and you need the cowl to be pushed up a bit... this is like having a 3rd hand. literally stick a mechanic's light under the cowl and use it for light and a jammer.



Soundaktor Delete by Ryan Philly, on Flickr

- 4. when ibcnum1 mentions the TAB (in his youtube), that is what you need to push. I am able to get my hands in there, but I couldn't push it off. remember the car is brand new, so I probably wasn't pushing hard enough.
- I grabbed a very long carpenter's screwdriver.

  I put the edge into that tab and turned/pushed at the same time and it came off in 2 seconds. this is the best way to get that harness off.
- 5. I really do not believe in leaving that part in the cabin for no reason. plus removing it, gives you the ability to tie down the harness, check this out.

once you remove the harness from the device, you need to get a 10mm socket and 1/4" driver. remove the bolts from the device. use caution when removing the bolts and handling the tools, so you don't end up with a hitchhiker in your engine bay. these bolts are simple to turn, after around 2-3 turns with the wrench, I turned the rest by hand.



Soundaktor Delete by Ryan Philly, on Flickr

6. now you have the harness. I opened it to see what was in there and if it could be broken down further (no).



Soundaktor Delete by Ryan Philly, on Flickr



Soundaktor Delete by Ryan Philly, on Flickr

then I used a black piece of tape (I happen to have some black tape that is similar to shipping tape, but a bit stronger). seal it off really well, push the tape into the area where the harness was. you can seal this thing off completely with tape



Soundaktor Delete by Ryan Philly, on Flickr

7. get a piece of outdoor 3M-type, double sided tape. put a piece on the flat side of the harness, that you sealed off. now put that flat side down onto the platform that originally hosted the device.



Soundaktor Delete by Ryan Philly, on Flickr



Soundaktor Delete by Ryan Philly, on Flickr

As you can see above, the result is "nothing to see here". I realize this is probably overkill for this stupid pos soundaktor delete, but I'm sure there's someone as anal as me out there, hopefully you'll benefit from this approach.

It weighs about the same as a hockey puck



Soundaktor Delete by Ryan Philly, on Flickr

Cheers

Last edited by RyanA3; 05-26-2013 at 01:57 AM.



Reply With Quote | P4

fester o

Junior Member

Join Date: Dec 20th, 2002 Location: Chicago Posts:

Vehicles: 2013 Golf R 05-26-2013 04:37 PM Reply #159

Thanks to all the helpful advice in this thread. I was able to disconnect and cover/tape up my Soundaktor successfully after 20 mins of fiddling around. Even though I was warned, I still managed to cut my knuckle during the process. 📀 Totally worth it, though, huge, huge improvement in the cabin noise. Coming from a 2003 Passat 1.8T, I love being able to hear the turbo spooling up again.



