

2010 UG

Touring Car Champion

Drives: United Gray MKVI GTI Join Date: Mar 2010 Location: Houston, TX Posts: 222

Front Door Panel Removal Write-up

I've had a couple PM's about doing a write-up on the door panel removal, so here goes. My pictures didn't really come out as well as I would have and I didn't take near enough of them, but I think I have enough to explain this clearly. All the pictures below are of the <u>driver's side of a 3-door</u>.

Tools needed:

Some sort of prying tool (screwdriver, butter knife, panel tool)


Torx T30 bit or driver

If you are using torx bits on a ratchet you'll need at least a 3 inch extension

You also might want to pick up some spare clips for the door panel (more on that later)


Step 1:

First thing you need to do is remove the small panel that sits just below the armrest. It is the piece that is removed in this picture:



The red arrow indicates where you should start to pry the piece upwards, it starts to pop up pretty easily and you shouldn't have to use much pre Work your way around the piece carefully pulling towards you and slightly upward. Once you reach the rear you should be able to slide it forward. careful not to pull the rear section straight out, as it is looped in behind the main panel and you might break something. Once you have it remove aside.

Step 2: Now its time to remove the three torx screws holding the panel in place. All three are the same size, T30. The are located in this picture by the grarrows.



Make sure not to misplace any of the screws

Step 3: Now that the screws are removed the panel is help in place by 7 clips on the underside of the panel. This picture of the back of the door panel sho you locate them. remember this is the reverse side of the drivers door.



I had the most luck by starting with lower rear corner (bottom right in this pic) then sliding my hands under the panel and slowly moving towards of the car while slightly pulling towards my body. Try not to lift or pull down on the panel, but pull as straight outward as possible. Once you have to the three along the bottom move up along sides remembering to pull straight out.

Step 4:

Once you have released all the clips you can pull up on the door panel it should slide free of the door. At this point it would be wise to set a towel something soft on the ground to rest the door panel on while you unclip the door lock wires and such from the panel. I didnt get a picture of how before I unclipped the wires but I can tell you that there are 4 or 5 harnesses all located around the window controls and the door latch mechanis highlighted in this picture:





the latch mechanism simply unclip from the panel by pulling on it, and all the wires unclip in a fairly straight forward manner. make sure not to fo about the little blinking red light thingy on the top of the drivers side panel.

Then we get to the whole reason I started this mini-project; the door speaker. As you can see from this pic, replacing it is going to be quite a bitcl speaker and mounting ring are one solid unit that is riveted to the inner door panel.



Time for re-installation. Its basically the same steps in reverse with a couple of minor differences. the first is that you need to make sure that the plastic rivets are are not still in the locked position, you can tell the difference by looking at these two pics I blatantly stole from someone else's w The first is of the clip in a locked position (not what you want), the second is the unlocked position which is what you are shooting for.





Apparently these things have a tendency to break or get stuck in the door, I guess I was lucky. Either way its probably best to pick up a couple sp the dealership or whatever.

After that, the easiest way to get the panel back on is to remove the felt window strip from the panel by pulling it down away from the door panel off pretty easy. Going back to the picture from step 3 you can see it as the dark strip at the top. here it re-installed on the door:

Once you've got that done, its a pretty simple. the main thing is to make sure that doors lock and unlock properly after re-attaching the latch cab seemed pretty idiot-proof to me, but you never know.

Like I said, this is my first write-up so be patient with me please.

Justin

Last edited by 2010 UG; 04-13-2010 at 11:16 AM.





■ 04-12-2010, 11:50 PM

Thank you for this, and I hope you don't mine me linking this thread in my CF-wrap thread! siagolf

Rally Car Newbie 2010 Deep Black Pearl 6-spd GTI

Engine: APR Stage 1, Carbonio CF Intake, Raven's Stealth Noise Pipe Plug, S3 Intercooler w/AWE hoses, AWE Turbo Discharge Pipe Tranny/Driveline: Neuspeed Torque Arm Insert

Drives: 2010 Blk MK6 GTI Join Date: Jan 2010 Location: Vancouver, BC, Canada

Tranny Driveline: Neuspeed Indige Arm Insert Suspension: HAR Touring Cup Willer Shoes: 19th Neuspeed RS10 Forged wiFalken FK-452 || 18th Defroits wiP-Zero Nero Interior: Leather, Dynaudio, Navi, MDI, Bluetooth, 3M Di-Noc Carbon Fiber Wrap Exterior: Reger Front Lip+Spiller, 4500k Fogs, Color-matched reflectors

Posts: 309







■ 04-13-2010, 10:24 AM

TDR-380 Formula 2 Champion

Very good write-up! I think the size of the Torx bit is T20. At least that's what it is for the 4 bolts that hold the head-unit in place 🕦



Newbie

Drives: 2012 Candy White GTI w/Convenience Join Date: Dec 2011 Location: San Jose, CA Posts: 1

Thank you for the write up. I was able to replace my mashed driver side mirror on my 2 week old 2012 GTI and only had to pay for parts (\$250) the painted cap was the only part that wasn't damaged 🙂

One addition to your writeup - don't know if its new for 2012 but in step 2 there are 4 T30 torx screws to remove. The pic is slightly different than my door so there might have been an extra screw added to the door. The added screw to is closest to the door latch. Just FYI to any 2012 GTIs that are getting the door panels removed.

John







■ 12-17-2011, 02:15 AM

McQueen77 Formula 1 Driver



Drives: "We only make one thing..." Join Date: Dec 2010

Location: Not Kentucky Posts: 8,730



Thanks to the OP for this write up. I followed it pretty closely when removing my panel the other day. Wasn't nearly as hard as I thought it would be.







#11

■ 12-17-2011, 12:04 PM

RuckU2 Rally Car Newbie

Drives: 2012 VW Golf 2.5l Join Date: Sep 2011 Location: Minot, ND Posts: 273



awesome write up...thank you!!!!







■ 12-17-2011, 01:04 PM

GTI likeurmom GolfMK6 Elite



Drives: Veyron 16.4 Join Date: Jul 2010 Location: woke up in a new

Bugatti Posts: 19,153

im not trying to jack your thread but whatever happened to the p2spec door panel removal how to???



Quote:

Originally Posted by GOBbluth 2

I cut the tether off. When I get to the pump, I remove the cap and chuck it into the nearest bush, patch of trees, or some sort of wet lands. I pump gas. Then I spend anywhere from 5 to 165 minutes retrieving the cap. I screw it back on and drive away. I'm not letting it dangle against the paint and I don't know any better way.









#13

■ 12-17-2011, 02:47 PM

RuckU2 Rally Car Newbie

Drives: 2012 VW Golf 2.5l Join Date: Sep 2011 Location: Minot, ND Posts: 273

Originally Posted by GTI_likeurmom 2

im not trying to jack your thread but whatever happened to the p2spec door panel removal how to???

http://golfmk6.com/forums/showthread...pec+door+panel

Search is your friend....Schooled by the newbie.....







■ 12-17-2011, 03:25 PM

GTI likeurmom GolfMK6 Elite



Drives: Vevron 16.4 Join Date: Jul 2010 Location: woke up in a new Posts: 19,153

Originally Posted by RuckU2 [2]

http://golfmk6.com/forums/showthread...pec+door+panel

Search is your friend....Schooled by the newbie.....



ok i explain. my computer doesnt work so i surf the web on my ps3, which doesnt work the best. i wasnt sure if the p2spec writeup was still around.

MY GTI MKVI



Quote:

Originally Posted by GOBbluth 🔰

I cut the tether off. When I get to the pump, I remove the cap and chuck it into the nearest bush, patch of trees, or some sort of wet lands. I pump gas. Then I spend anywhere from 5 to 165 minutes retrieving the cap. I screw it back on and drive away. I'm not letting it dangle against the paint and I don't know any better way.



tmiw

■ 01-20-2012, 02:02 AM

Formula 5000 Driver

Location: San Diego Posts: 1,544



Quote:

Originally Posted by jmalian 💟

sweet, maybe I'll fix my speaker rattle!

One addition to your writeup - don't know if its new for 2012 but in step 2 there are 4 T30 torx screws to remove. The pic is slightly different than my door so there might have been an extra screw added to the door. The added screw to is closest to the door latch. Just FYI to any 2012 GTIs that are getting the door panels removed.

That may be why I couldn't get the door panel off at all today while I was trying to install my door lights. Is there additional trim I need to remove to get to the 4th screw? I don't remember seeing a 4th screw anywhere.

2012 Candy White GTI w/Autobahn and DSG (Journal thread)

Tons of stuff.







■ 01-20-2012, 07:17 AM

Drives: 2012 GTI 4dr Autobahn w/DSG Join Date: Feb 2011

DSGVW Formula 3000 Driver




Drives: 2012 CSG GTI DSG Join Date: Oct 2011 Location: USA Posts: 3,854





■ 01-22-2012, 01:37 AM

I took a look again and I found the 3rd screw (or is it 4th?) this time. Was able to remove the front driver's door with a tmiw bunch of force and only ended up with one door clip that was locked. I only installed the door lights for that door since it Formula 5000 Driver was 10pm by then--I'll do the rest tomorrow. How do you unlock the door clips, btw?



Powered by vBulletin® Version 3.7.2 Copyright ©2000 - 2016, Jelsoft Enterprises Ltd.